

# Solenoid valves JMN2H, ISO 15 407-1



Technical data – 5/2-way valves, double solenoid

Ordering data – ISO size 01					
Circuit symbol	Description	Voltage	Central plug <sup>1)</sup>	Part No.	Type
	Internal pilot air supply	12 V DC, 24 V AC	–	<b>187 880</b>	<b>JMN2H-5/2-01-12DCA</b>
		24 V DC	–	<b>161 071</b>	<b>JMN2H-5/2-D-01<sup>2)</sup></b>
		110 V AC	–	<b>161 884</b>	<b>JMN2H-5/2-D-01-110AC</b>
		230 V AC	–	<b>161 898</b>	<b>JMN2H-5/2-D-01-230AC</b>
		24 V DC	■	<b>191 319</b>	<b>JMN2H-5/2-01-ZSR<sup>2)</sup></b>
	External pilot air supply	12 V DC, 24 V AC	–	<b>187 881</b>	<b>JMN2H-5/2-01-S-12DCA</b>
		24 V DC	–	<b>161 072</b>	<b>JMN2H-5/2-D-01-S<sup>2)</sup></b>
		110 V AC	–	<b>161 885</b>	<b>JMN2H-5/2-D-01-S-110AC</b>
		230 V AC	–	<b>161 899</b>	<b>JMN2H-5/2-D-01-S-230AC</b>
		24 V DC	■	<b>191 320</b>	<b>JMN2H-5/2-01-S-ZSR<sup>2)</sup></b>
	With dominant signal at 14, internal pilot air supply	12 V DC, 24 V AC	–	<b>187 882</b>	<b>JMN2DH-5/2-01-12DCA</b>
		24 V DC	–	<b>161 073</b>	<b>JMN2DH-5/2-D-01<sup>2)</sup></b>
		110 V AC	–	<b>161 886</b>	<b>JMN2DH-5/2-D-01-110AC</b>
		230 V AC	–	<b>161 900</b>	<b>JMN2DH-5/2-D-01-230AC</b>
		24 V DC	■	<b>191 321</b>	<b>JMN2DH-5/2-01-ZSR<sup>2)</sup></b>
	With dominant signal at 14, external pilot air supply	12 V DC, 24 V AC	–	<b>187 883</b>	<b>JMN2DH-5/2-01-S-12DCA</b>
		24 V DC	–	<b>161 074</b>	<b>JMN2DH-5/2-D-01-S<sup>2)</sup></b>
		110 V AC	–	<b>161 887</b>	<b>JMN2DH-5/2-D-01-S-110AC</b>
		230 V AC	–	<b>161 901</b>	<b>JMN2DH-5/2-D-01-S-230AC</b>
		24 V DC	■	<b>191 322</b>	<b>JMN2DH-5/2-01-S-ZSR<sup>2)</sup></b>

1) Included in the scope of delivery

2) Free of copper and PTFE