

Hot Mounting



ConduFast

Acrylic hot mounting resin with iron powder filler. Thermoplastic. Electrically conductive

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100039	RESFE	Net 1 kg

SpeciFast

Acrylic hot mounting resin. Transparent. Thermoplastic

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100041	RESYV	Net 7.5 kg
40100050	RESFA	Net 25 kg
40100051	RESTH	Net 1 kg

PolyFast

Phenolic hot mounting resin with carbon filler, for edge retention and examination in SEM. Thermosetting

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100036	FAPSA	Net 1 kg
40100037	FAPME	Net 7.5 kg

IsoFast

Diallylphtalate hot mounting resin with glass fibre filler, for edge retention and planeness. Thermosetting

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100042	RESDI	Net 1 kg
40100043	RESTY	Net 7.5 kg

DuroFast

Epoxy hot mounting resin with mineral filler, for edge retention and planeness. Thermosetting

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100044	RESIF	Net 1 kg
40100045	RESEN	Net 7.5 kg

MultiFast

Phenolic hot mounting resin, black, for general use. Thermosetting

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100027	RESRU	Net 2.5 kg
40100028	RESUK	Net 7.5 kg
40100029	RESLA	Net 25 kg

MultiFast Green

Phenolic hot mounting resin, green. Thermosetting

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100030	FAGSA	Net 2.5 kg
40100031	FAGME	Net 7.5 kg

MultiFast Brown

Phenolic hot mounting resin, brown. Thermosetting

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40100033	FABSA	Net 2.5 kg
40100034	FABME	Net 7.5 kg
40100035	FABLA	Net 25 kg

Pre-mount

Phenolic hot mounting resin in tablet form, for easy handling. Thermosetting

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40101001	RESUN	For cylinder dia. 25 mm / 1", height 16 mm. Net weight 10 kg (approx. 1100 pcs.)
40101003	RESGI	For cylinder dia. 30 mm / 1 ¼", height 16 mm. Net weight 10 kg (approx. 760 pcs.)
40101005	RESAM	For cylinder dia. 40 mm / 1 ½", height 16 mm. Net weight 10 kg (approx. 460 pcs.)

Others

AntiStick

Mould release agent to avoid sticking of hot mounting resin to the rams of the mounting presses. Stearate powder in applicator

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40300043	FASTI	Net 8 g

Heat Conductive Paste

For effective heat transfer between heating cooling unit and cylinder in (old) hot mounting presses

<i>Cat.no</i>	<i>Code</i>	<i>Specification</i>
40300001	PREPA	Net 25 g