

SINUMERIK 840D

NCU 561.4

Order no.	6FC5 356-0BB14-0AA0	6FC5 357-0BB14-0AA0	6FC5 357-0BB24-0AA0	6FC5 357-0BB34-0AA0
Product name	SINUMERIK 840D powerline NCU 561.4	SINUMERIK 840D powerline NCU 571.4	SINUMERIK 840D powerline NCU 572.4	SINUMERIK 840D powerline NCU 573.4
Processor	Celeron			Celeron
● Clock frequency	400 MHz			650 MHz
SIMATIC S7 - integrated	PLC 314C-2 DP			
Input voltage	Via SIMODRIVE device bus			
Degree of protection to EN 60529 (IEC 60529)	IP 20 (with NCU box)			
Humidity rating in accordance with EN 60721-3-3	Class 3K5 condensation and icing excluded. Low air temperature 0°C (+32°F)			
Relative atmospheric humidity				
● Storage	10 ... 95%			
● Transport	10 ... 95%			
● Operation	< 95% for 1 h, annual average < 65%			
Ambient temperature				
● Storage	-20 ... +60 °C (-4 ... +140°F)			
● Transport	-20 ... +60 °C (-4 ... +140°F)			
● Operation	0 ... +55°C (+32 ... +131°F)			
Weight, approx.	0.72 kg (1 lb 9 oz)			1.05 kg (2 lb 5 oz)
Dimensions				
● Width	50 mm (1.96 in)			
● Height	316 mm (1.036 ft)			
● Depth	207 mm (8.14 in)			