

## DP/DP transceiver



<b>DP/DP transceiver</b>	
PROFIBUS transfer rate	max. 12 Mbit/s
Interfaces	
<ul style="list-style-type: none"> <li>● PROFIBUS DP</li> </ul>	9-pin sub-D connector
Supply voltage	24 V DC
Current consumption typ.	150 mA
Mounting	Upright (DIP switches above)
Perm. environmental conditions	
<ul style="list-style-type: none"> <li>● Operating temperature</li> </ul>	
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>· horizontal mounting</li> </ul> </li> </ul>	0°C to +60°C
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>· all other mounting positions</li> </ul> </li> </ul>	0°C to +40°C
<ul style="list-style-type: none"> <li>● Transport/storage temperature</li> </ul>	-40 °C to +70 °C
<ul style="list-style-type: none"> <li>● Relative humidity</li> </ul>	10-95 % at +25 °C
Design	
<ul style="list-style-type: none"> <li>● Dimensions (W x H x D) in mm</li> </ul>	40 x 127 x 117
<ul style="list-style-type: none"> <li>● Weight</li> </ul>	Approx. 250 g
Degree of protection	IP20