

Magnetventile JMN2H, ISO 15 407-1



Datenblatt – 5/2-Wegeventile, Magnet-Impulsventile

Bestellangaben – ISO-Größe 01					
Schaltzeichen	Beschreibung	Spannung	Zentralstecker ¹⁾	Teile-Nr.	Typ
<p>14 4 2 12 5 1 3 83 (12)</p>	Steuerluftversorgung intern	12 V DC, 24 V AC	–	187 880	JMN2H-5/2-01-12DCA
		24 V DC	–	161 071	JMN2H-5/2-D-01²⁾
		110 V AC	–	161 884	JMN2H-5/2-D-01-110AC
		230 V AC	–	161 898	JMN2H-5/2-D-01-230AC
		24 V DC	■	191 319	JMN2H-5/2-01-ZSR²⁾
<p>14 4 2 12 81 (14) 5 1 3 83 (12)</p>	Steuerluftversorgung extern	12 V DC, 24 V AC	–	187 881	JMN2H-5/2-01-S-12DCA
		24 V DC	–	161 072	JMN2H-5/2-D-01-S²⁾
		110 V AC	–	161 885	JMN2H-5/2-D-01-S-110AC
		230 V AC	–	161 899	JMN2H-5/2-D-01-S-230AC
		24 V DC	■	191 320	JMN2H-5/2-01-S-ZSR²⁾
<p>14 4 2 12 5 1 3 83 (12)</p>	mit dominierendem Signal bei 14 Steuerluftversorgung intern	12 V DC, 24 V AC	–	187 882	JMN2DH-5/2-01-12DCA
		24 V DC	–	161 073	JMN2DH-5/2-D-01²⁾
		110 V AC	–	161 886	JMN2DH-5/2-D-01-110AC
		230 V AC	–	161 900	JMN2DH-5/2-D-01-230AC
		24 V DC	■	191 321	JMN2DH-5/2-01-ZSR²⁾
<p>14 4 2 12 81 (14) 5 1 3 83 (12)</p>	mit dominierendem Signal bei 14 Steuerluftversorgung extern	12 V DC, 24 V AC	–	187 883	JMN2DH-5/2-01-S-12DCA
		24 V DC	–	161 074	JMN2DH-5/2-D-01-S²⁾
		110 V AC	–	161 887	JMN2DH-5/2-D-01-S-110AC
		230 V AC	–	161 901	JMN2DH-5/2-D-01-S-230AC
		24 V DC	■	191 322	JMN2DH-5/2-01-S-ZSR²⁾

1) Im Lieferumfang enthalten

2) Kupfer- und PTFEfrei