ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MOR

Item # 102441, Oilube® Powdered Metal Br

Isostatic Oilube® Thrust Washers

- Standard stock products
- SAE 841-copper (87-90%), tin (8-9), carbon, oth
- Powdered metal bronze providing interconnecte
- Vacuum impregnated with SAE 30 oil during the
- Self-lubricating – when in motion oil rises to the
- Ideal for heavy loads at moderate speeds or ligh
-

+ more



Dimensions | Specifications | Tolerances | Performan

Dimensions –

Detailed Description	
Nominal Inner Diameter	1 in
Nominal Outer Diameter	1 5/8 in
Nominal Thrust Washer Thickness	1/16 in

Specifications –

Catalog Number	TT-1603-3
Interchange #	TT160303 TT1603-3

Unit of Measure	Each
Material	Powdered Metal / Oil Impregnated Bronze
Material Standard	SAE 841
Avg Unit Weight	0.0181 lb
UPC Code	00846802010379

Tolerances

Inner Diameter Tolerance	±.005 in
Outside Diameter Tolerance	±.015 in
Thrust Washer Thickness Tolerance	±.0025 in

Performance Data

Load - P Max Value	2,000 lb/in²
Speed - V Max Value	1,200 ft²/min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	50,000