
DATASHEET

Crimped wheel brush



ArtNr. 366342

Wheel brushes RB dia 200 x 28-30 mm EBR 26 mm EBA 29 mm tube 80 mm steel wire stainless ROF crimped 0.20 mm bore 50.8DKN mm 13x7 mm adaptor set Ø50.8+DKN/ Ø30/1"/22.2/20/16/ Ø1/2"/12 trim length 37.5 mm



Characteristics

Technical data

Art. Description ERP	Wheel brushes RB dia 200 x 28-30 mm EBR 26 mm EBA 29 mm tube 80 mm steel wire stainless ROF crimped 0.20 mm bore 50.8 DKN mm 13x7 mm adaptor set Ø50.8+DKN/ Ø30/1"/22.2/20/16/ Ø1/2"/12 trim length 37.5 mm
Filling Material Diameter	0.20 mm
Net weight	1.154 kg
Filling Width [A]	28-30 mm
Number of Rows [RZ]	2
Double Keyway [DKN]	13x7
Tube Adapter Set [RED]	Ø50.8+DKN/ Ø30/1"/22.2/20/16/ Ø1/2"/12
Tube Diameter [R]	80 mm
RPM max.	4500
Brush Diameter [D]	200 mm
Filling Height [H]	37.5 mm
Bore Diameter [DB]	50.8DKN mm
Clamping Width Tubular Rivet [EBR]	26 mm
Bore Diameter Maximum [DBmax]	80 mm
Bore Diameter Minimum [DBmin]	16 mm
Clamping Width Metal Disc [EBA]	29 mm
Filling material	ROF
Filling Material Shape	Crimped
Art. Group	Wheel brushes RB

Order information

ArtNr	366342
EAN	4017359084052
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Chemical industry | Skilled trades | Plastics industry | Medical equipment industry | Metalworking industry
Application	Wire stripping | Roughening | Deburring | Removing paint | Derusting | Polishing | Cleaning
Application Description	The wheel brush is used for deburring, roughening, stripping, polishing, cleaning, and removing rust and paint.
Article Description Marketing	Crimped wheel brush
On Stock as per Catalogue	No
Catalogue Page	34
Product Description short	Wheel brush with a diameter of 200 mm, bore diameter of 50.8 mm, double keyway, adapter sets 4 and 1 and stainless steel wire filling

Product Description long	The wheel brush is mainly used for deburring work in stationary machines or machining centres. The version with stainless steel wire is used on stainless steel and aluminium surfaces. This wheel brush is suitable for the following applications: Removing rust, paint, dirt, etc., and for roughening, deburring, stripping and polishing. The wire and tube diameters are determining factors for choosing the right article. The version with a large tube diameter (dimension R) contains more wire, offers harder action, and has a longer service life. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking, in automotive supply and construction firms, as well as in the plastics, rubber, chemical and medical equipment industries.
Keywords	Automotive industry | Construction industry | Chemical industry | Skilled trades | Plastics industry | Medical equipment industry | Metalworking industry | Wire stripping | Roughening | Deburring | Removing paint | Derusting | Polishing | Cleaning | Aluminium | Stainless steel | Copper | Steel | Titanium | Zinc | Stainless steel wire | ROF | Wheel brushes | Crimped | bore
Processed Surface	Aluminium | Stainless steel | Copper | Titanium | Zinc

Description

Wheel brushes
Wheel brushes from LESSMANN are used for a variety of purposes in surface finishing. They are ideal for removing rust, paint, or dirt, and for roughening, deburring, stripping and polishing.