ROBUR 8094

lifting chain sling, 4 legs grade 8



Manufactured with high-strength components, Robur lifting pendants are suitable for intensive and continuous use in total safety.

Designed in compliance with EN 818-4, the chain pendants are assembled in the Sulmona factory by competent and adequately trained personnel and guarantee compliance with the safety requirements of Italian Legislative Decree 81.





Certifications and Standards:

CE EN 818-4

WORKING LOAD AND DURABILITY
High-tensile alloy steels allow high mechanical performance and ensure long life.

SUITABLE FOR HEAVY-DUTY USE
Designed for continuous and repeated use at maximum capacity.

WIDE TEMPERATURE RANGE OF USE
The quality of the materials used allows them to be used at both low and high temperatures (-40°/+200°) without any change in mechanical and performance characteristics.

ENABLES BALANCED LIFTS
The four anchor points with which the pendant is equipped facilitate load balancing.

Scan the QR Code to access the web tab
Specs, media and documentation in one click.

ROBUR 8094

lifting chain sling, 4 legs grade 8

Technical Specifications

Dimensions



Certifications and Standards:

CE EN 818-4

Coded items

	Art.	D mm	L m	WLL ton
080940001	8094 D6-1	6*	1	2,36
080940002	8094 D6-2	6*	2	2,36
080940003	8094 D6-3	6*	3	2,36
080940004	8094 D6-4	6*	4	2,36
080940021	8094 D7-1	7*	1	3,15
080940022	8094 D7-2	7*	2	3,15
080940023	8094 D7-3	7*	3	3,15
080940024	8094 D7-4	7*	4	3,15
080940041	8094 D8-1	8*	1	4,25
080940042	8094 D8-2	8*	2	4,25
080940043	8094 D8-3	8*	3	4,25
080940044	8094 D8-4	8	4	4,25
080940051	8094 D10-1	10*	1	6,7
080940052	8094 D10-2	10	2	6,7
080940053	8094 D10-3	10	3	6,7
080940054	8094 D10-4	10	4	6,7
080940131	8094 D13-1	13	1	11,2
080940132	8094 D13-2	13	2	11,2
080940133	8094 D13-3	13	3	11,2
080940134	8094 D13-4	13	4	11,2
080940161	8094 D16-1	16	1	17
080940162	8094 D16-2	16	2	17
080940163	8094 D16-3	16	3	17
080940164	8094 D16-4	16	4	17
080940172	8094 D20-2	20	2	26,5
080940173	8094 D20-3	20	3	26,5
080940174	8094 D20-4	20	4	26,5

Scan the QR Code to access the web tab
Specs, media and documentation in one click.