Cover PDS-LUK

Ref. B17076M

Ref. arch 17076



APPLICATION

- LED protection and light diffusion in lighting fixtures


MOUNTING

- to the extrusion, by pressing

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Color	☐ **frosted**
Material	**PC**
Shape	**semicircular**
Maximum length on request	**19'8"**
Light transmission	**62 %**
Width	**0.51"**
Possibility of obtaining a line of light	**yes**

Length	Ref
39.37"	**B17076M_1** 17076_1
78.94"	**B17076M_2** 17076_2
9'11"	**B17076M_3** 17076_3

Cover PDS-LUK

Ref. B17076M

Ref. arch 17076

RELATED PROFILES > UNIVERSAL



KUBIK-45
A07697
Ref. arch B7697



OLEK
A08505
Ref. arch B8505