650098-000 ✔ ACTIVE

RAYCHEM

TE Internal #: 650098-000

Splices, 20 – 16 AWG Wire Size, .61 – 1.21 mm² Wire Size, Sealable, Splice Kit, .067 in [1.69 mm] Barrel Inside Diameter, 1216 – 2426 CMA Wire Size

Terminals & Splices > Splices



Wire Size: **.61 – 1.21 mm²**

Sealable: **Yes**

Splice Features: **Splice Kit**

Barrel Inside Diameter: **1.69 mm [.067 in]**

Features

Product Type Features

Splice Accessory Type	Splice
Sealable	Yes
Serrated	No
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Number of Serrations	0
Compatible With Wire & Cable Type	Discrete Wire

Body Features

Insulation Material	Modified Polyvinylidene
Splice Features	Splice Kit
Primary Product Material	Copper Alloy

Contact Features

Barrel Type	Closed

Dimensions

Wire Size	1216 – 2426 CMA
Barrel Inside Diameter	1.69 mm[.067 in]
Overall Product Length	29.21 mm[1.15 in]

Usage Conditions

Insulation Option	Fully Insulated
Operating Temperature Range	-55 – 150 °C[-67 – 302 °F]

Operation/Application

Heavy Duty	No

Industry Standards

Government Qualified Splice	No

Packaging Features

Packaging Method	Bag/Box

Product Compliance

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

Compatible Parts



TE Part # 1752939-1
SDE DIE-26-12 MINI SEAL SPLICE



TE Part # 992008-000
AD-1377-CRIMP-TOOL-3-CVTY

Documents

Product Drawings

D-436-75

English

Datasheets & Catalog Pages

1654025_Sec8_D-436

English

Harness Repair Products Quick Reference Guide

English