Gigabit Ethernet special Switch

DIGITUS®

								
Part number	DN-651107	DN-651126	DN-651106	DN-651109	DN-651108	DN-651127	DN-651113	DN-651110
Product Name	Industrial 5-Port Gigabit Switch DIN rail, extended temp. Range	Industrial 5-Port Gigabit Switch DIN rail, extended temp. Range	4-port 10/100/1000BASE-TX+1000Base- 2 FX Industrial Ethernet Switch	Industrial Gigabit Ethernet PoE+ Switch 4-port PoE + 2-port SFP, 802.3at, DIN rail	Industrial Gigabit Ethernet Switch 8-port, DIN rail, extended temp. range	Industrial 8-Port Gigabit Flat Switch 8-port, DIN rail, extended temp. range	Industrial 7-port Gigabit PoE+Switch + 1 PD-port IEEE802.3af/at, DIN rail, extended temp. range	Industrial Gigabit Ethernet PoE+ Switch 8-port PoE + 2-port SFP, 802.3at, DIN rail
Number of ports	5 Port	5 Port	4 Port	4 Port	8 Port	8 Port	7 Port	8 Port
Number of ports (Uplink)	⊗	⊗	2 Port	2 Port	⊗	⊗	1 Port (PD Port, max. 95 W)	2 Port
Uplink port connection	⊗	⊗	SFP	SFP	⊗	⊗	RJ45	SFP
PoE (Power over Ethernet)	⊗	⊗	⊗	✓	⊗	⊗	✓	✓
Number of PoE ports	⊗	⊗	⊗	4	⊗	⊗	7	4
Standard 802.3af (PoE Type 1)	⊗	⊗	⊗	✓	⊗	⊗	✓	✓
Standard 802.3at (PoE Type 2)	⊗	⊗	⊗	✓	⊗	⊗	✓	✓
Standard 802.3bt (PoE Type 3)	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗
Standard 802.3bt (PoE Type 4)	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗
Total PoE Power budget (W)	⊗	⊗	⊗	120 W	⊗	⊗	240 W	120 W
Maximum Power/ Port (W)	⊗	⊗	⊗	30 W	⊗	⊗	30 W	30 W
Managed	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗
Industrial usage	✓	✓	✓	✓	✓	✓	✓	✓
Installation type	DIN Rail	DIN Rail	DIN Rail	DIN Rail	DIN Rail	DIN Rail	DIN Rail	DIN Rail
Automatic cable detection - Auto MDI / MDI-X function	✓	✓	✓	✓	✓	✓	✓	✓

All brand names and logos that are mentioned are trademarks or registered trademarks of the respective owners. The right to make design-related variations from the photos, mistakes and technical changes is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved and subject to availability. Published by ASSMANN Electronic GmbH, Aufdem Schüffel 3, 58513 Lüdenscheid - Germany. 03/2023

Gigabit Ethernet special Switch

DIGITUS®

Part number	DN-651107	DN-651126	DN-651106	DN-651109	DN-651108	DN-651127	DN-651113	DN-651110
Supported standards: IEEE 802.3 10BaseT, IEEE 802.3u 100 BaseTX, IEEE802.3ab 1000BaseTX	✓	✓	✓	✓	✓	✓	✓	✓
Supported: IEEE802.3x Flow Control und Back Pressure	✓	✓	✓	✓	✓	✓	✓	✓
Supported: Store and forward technology for optimized data transfer	✓	✓	✓	✓	✓	✓	✓	✓
Automatic speed and half/full duplex recognition/adjustment	✓	✓	✓	✓	✓	✓	✓	✓
Backplane	10 Gbps	10 Gbps	10 Gbps	12 Gbps	16 Gbps	16 Gbps	16 Gbps	20 Gbps
Size of MAC addresses Table	8K	4K	4K	4K	8K	4K	4K	4K
Housing	Compact, robust metal housing	Compact, flat, robust metal housing	Compact, robust metal housing	Compact, robust metal housing	Compact, robust metal housing	Compact, flat, robust metal housing	Compact, robust metal housing	Compact, robust metal housing
Short-circuit protection	✓	✓	✓	✓	✓	✓	✓	✓
Lightning and overvoltage protection	✓	✓	✓	✓	✓	✓	✓	✓
Suitable for DIN rail (top-hat rail) mounting	✓	✓	✓	✓	✓	✓	✓	✓
Redundant power supply with reverse polarity protection function	✓	✓	✓	✓	✓	✓	✓	✓
Power supply	12~48 V DC, 18~ 36 V AC	12~48 V DC,	12~56 V DC,	48~57 V DC,	12~56 V DC,	12~48 V DC,	48~57 V DC,	48~57 V DC,
VLAN	✗	✗	✗	✗	✗	✗	✗	✗
Removable terminal connection	✓	✓	✓	✓	✓	✓	✓	✓
Protection class	IP40	IP40	IP40	IP40	IP40	IP40	IP40	IP40
Outdoorsuitable	✗	✗	✗	✗	✗	✗	✗	✗
Protection against vanadlism	✗	✗	✗	✗	✗	✗	✗	✗
Extended operating temperature range	-40 °C ~ +80 °C	-40 °C ~ +80 °C	-40 °C ~ +80 °C	-40 °C ~ +75 °C	-40 °C ~ +80 °C	-40 °C ~ +80 °C	-20 °C ~ +70 °C	-40 °C ~ +75 °C
suitable for non-con-densing humidity	5% to 95%	5% to 95%	5% to 95%	5% to 90%	5% to 95%	5% to 95%	10% to 90%	5% to 95%

All brand names and logos that are mentioned are trademarks or registered trademarks of the respective owners. The right to make design-related variations from the photos, mistakes and technical changes is reserved. All information is provided without guarantee. We assume no liability for printing errors. The right to delivery is reserved and subject to availability. Published by ASSMANN Electronic GmbH, Aufdem Schüffel 3, 58513 Lüdenscheid - Germany. 03/2023