



LightGuard® 350 Sealed Fiber Optic Splice Closure

The LightGuard (LG) 350 is a sealed dome closure designed for large count fiber splicing (up to 480 single or 1152 mass) in a butt configuration. Utilized in aerial or underground environments where a sealed closure is required, the LG-350 is ideal for express, ring or long haul applications and requires only a common can wrench for installation.

Features

- Supports stranded loose tube or ribbon fiber cables in either armored or dielectric configurations
- Installation and re-entry requires only a common can wrench
- Fully sealed to protect fiber and splices ensuring longevity
- Fully kitted with all parts to install five cables
- Designed and tested to Telcordia® GR-771 requirements
- Rural Utilities Service (RUS) Listed

Telcordia is a registered trademark of Telcordia Technologies, Inc.

Specifications

PARAMETER	VALUE	
Splice Capacity (Max.)—Single, Mass, Mechanical	480, 1152, 108	
Number of Splice Trays (Max.)—Single, Mass, Mechanical*	12, 8, 8	
Cable Entrance Configuration	Butt	
Cables	5 to 11	
Cable Sizes (Min. O.D. - Max. O.D.) Included Grommets	(2) Express Ports	(3) Drop Ports
Single in. (mm)	0.40" - 1.00" (10.0 - 25.4)	0.26" - 0.80" (6.6 - 20.0)
Additional Grommets		
Dual Express Port Only in. (mm)	0.26" - 0.44" (6.6 - 11.2)	
Quad Express Port Only in. (mm)	0.26" - 0.38" (6.6 - 9.7)	
(4) Flat Drop Port Only in. (mm)		0.19" x 0.34" (4.8 x 8.6) or 0.25" round (6.4)
Dimensions—(L x D) in. (mm)	28.0" x 10.0" (710.0 x 254.0)	
Weight - lbs. (kg)	16 (7.26)	

Ordering Information

DESCRIPTION	MODEL NO.	AFL NO.
LG-350 Fiber Optic Splice Closure—Stores 480 single fusion or 1152 mass fusion, includes (5) cable kits for sealing/retention and (2) ground terminals with removable bond. Not included: Splice Trays, Cable Grounding Kits or Hanger Brackets	LG-350-U-0	FC000009-PS
		0-02
LL-4896-R Mass Splice Tray—Stores (24) mass fusion splices (288 F). Maximum of 5 trays in the LG-350	LL-4896-R	FA000022
LL-4896-L Single Splice Tray—Stores (96) single fusion splices. Maximum of 5 trays in the LG-350	LL-4896-L	FA000023
LG-350 Single Grommet Kit (Min. 0.40" - Max. 1.00")—For use in LG-350/AC/SD on Express Port side	LG-350 Exp Single Kit	FC000726
LG-350 Dual Grommet Kit (Min. 0.26" - Max. 0.44")—For use in LG-350/AC/SD on Express Port side	LG-350 Exp Dual Kit	FC000337
LG-350 Quad Grommet Kit (Min. 0.26" - Max. 0.38")—For use in LG-350/AC/SD on Express Port side	LG-350 Exp Quad Kit	FC000421
LG-350 Single Grommet Kit (Min. 0.26" - Max. 0.80")—For use in LG-350/AC/SD on Drop Port side	LG-350 Drop Single Kit	FC000727
LG-350 Drop 4 Flat Drop Grommet Kit—For use with standard flat drop cable and round cable up to 0.25" O.D.	LG-350 Drop 4 Flat Kit	FC000422
Universal Aerial Strand Hanger Kit—For use with LG-150/250/350	Universal Hanger	FC000006
Extended Offset Strand Hanger Kit—For use with LG-150/250/350	Extended Offset Hanger	FC000208
Pole or Wall Mount Bracket—For use with LG-150/250/350	PWK	FC000592
OPGW Dual Cable Bracket Kit—For use with LG-150/250/350	OPGW Dual Bracket	FC000683
OPGW Quad Cable Bracket Kit for use when installing Sealed Closures—For use with LG-350	LG-350 OPGW Quad Bracket Sealed	FC000747
1x6 Fiber Router Kit with furcation tubes	1x6 Fiber Router	FC000070
Cable Grounding Kit (pack of 5)—Clamp-On Ground Cable Only	CGK-5	FC001091
*Mechanical Splice Kit. Includes 10 pieces of VHB tape. Used in all splice trays. Each piece holds 12 splices.	VHB Tape	FA000089
O-Ring and Lock Ring Kit—For use with LG-350/350AC/SD	LG-350 O-Ring Lock Ring Kit	FC000775

* See Accessory Specifications. See Splice Tray Specifications.