

3364.** RING TERMINALS · WITH INSULATION SUPPORT



Specification 8 mm Plate

Ø (mm) 5,2

Wire size mm² (AWG) 0,75-1,5 (18-16)

Ø Insulation (mm) 2,5-3,3

Materials, temperature and contact resistance

Part nr.	Material	Finishing	Max. Temp. (°C)
3364.00	Brass	Natural	110
3364.02	Brass	Tin plated	120

Material thickness (mm) 0,5

Application tool MN3358

Wire strip length 3.5 (±0.3) mm

Crimping parameters & pull out force

Wire section (±10%)	Conductor 		Insulator	Pull-out force (N)
	Height (mm)	Width (mm)	Width (mm)	
0.75 mm ²	1.65 (±0.05)	2.98 (±0.05)	4.08 (±0.10)	84N @ 60s
1.00 mm ²	1.70 (±0.05)	2.98 (±0.05)	4.09 (±0.10)	108N @ 60s
1.50 mm ²	1.85 (±0.05)	3.00 (±0.05)	4.10 (±0.10)	150N @ 60s



Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Winding number 8000

Approvals



Drawing





3364.**

RING TERMINALS · WITH INSULATION SUPPORT



Rev. Nr.	Concept	Date	Created/Revised	Approved
A2	Change company name and logo	2021-10-21	Laboratory Dept.	E. Roura
A1	Da		ept.	E. Roura